


**740 Series
High Speed
Vertical
Spin Trimmer**

mtm
S Y S T E M S



From Blow Molder to Box MTM Systems is Your Answer For Auxiliary Equipment

Features	Benefits
Heated blade technology	Gives the container a clean neck finish. Extends life of the blade. Virtually any resin will trim in the 740. Lower capital expenditure as one machine will work on many product lines.
New redesigned blade holder	Allows the blade to nest at the correct angle without a lengthy setup period. Reduced blade changeover time.
Micrometer blade adjustment	Faster and higher accuracy for better bottle finish.
Digital heater control	Precise temperature control providing a clean neck finish and longer blade life.
Belt guide wear strip	Increases belt life and higher productivity.
Exclusive automatic blade guard	Safer and allows quicker clearing of bottles.
Heavy duty 1/2 hp drive	Increased production speed.
Bottle jam detection and safety clutch drive	Detects bottle mistrims for auto shutdown and auto opening of the trimmer. Clutch disengages drive before any damage can occur. Less downtime.
PLC controls with panel mounted user interface	Reduces setup time and functions as a fault message panel.
Spring loaded quick change belt tensioning	Reduces chance for operator error during procedure. Increased productivity.
Infeed and discharge backup photo eyes	Shuts down the trimmer in the event of backup downstream of the trimmer or upstream of the trimmer.
Audible alarm and beacon lights for detection devices	Faster response time from plant staff.

Specifications

Dimensions:		Utility Requirement:	
Width	39"	Electrical Supply	
Length	67"	Voltage	240VAC/3 Phase
Height	60"	Amperage	15 Amp
Weight	1200 lbs.		
Vertical Height		Compressed Air Supply	
Range	41.5" ± 5" Height from floor to blade	Line Size	3/8" Pipe
		Pressure	90-100 psi
Motor Ratings:		Container Range:	
Trimmer	1/2 hp	Containers per minute	220 (depending on size)
Blower	3 hp	Min/Max neck size	1.5" – 7" 25 – 127 mm
Conveyor	1/2 hp	Min/Max diameter	1" – 4" 38 – 178 mm
Heater Blade Temperature	450°F (Max)	Min/Max height	3" – 18" 76 – 450 mm

Specifications are subject to change without notice. Guards are supplied and must be in place before operation. All sales are subject to our prevailing terms and conditions of sale. Other options available upon request.

Lectro Engineering Company
1643 Lotsie
St. Louis, MO 63132 USA

Phone 314-567-3100
Fax 314-567-3466
www.lectrotreat.com

DVD & CD available to show application & operation